



PROFESSIONAL & BROADCAST DISPLAY DIGITAL SIGNAGE

www.vity.com



email: info@vity.com
phone: +33 (0)2 97 89 20 02
fax: +33 (0)2 97 89 20 10

180 rue Pierre Landais - 56850
CAUDAN - FRANCE

LCD 2009

concise version

LCV xR SERIES - RACK MOUNT VIDEO

LCV 25X6R



Panel size 6x 2.5"
 Resolution 480 x 234
 Display area (mm) 49 x 37
 Pitch (mm) 0.1035 x 0.1035
 Brightness 250 cd/m²
 Contrast 350:1
 Viewing angles H: 50/50° - V: 15/35°
 Inputs 1x CVBS on BNC
 + loop + Tally
 Dimensions (WxHxD) 19" x 2U x 82 mm
 Power supply 12 VDC
 Consumption 24W

LCV 4X4R



Panel size 4x 4"
 Resolution 960 x 234
 Display area 82 x 61 mm
 Pitch (mm) 0.171 x 0.264
 Brightness 250 cd/m²
 Contrast 150:1
 Viewing angles H: 45/45° - V: 10/30°
 Inputs 1x CVBS on BNC
 + loop + Tally
 Dimensions (WxHxD) 19" x 3U x 162 mm
 Power supply 12 VDC
 Consumption 24W

LCV 4x4RHX - low cost model

Panel size 4x 4"
 Resolution 960 x 234
 Brightness 350 cd/m²
 Contrast 850:1

LCV 4x4RFSDI

Panel size 4x 4"- wide format
 Brightness 400 cd/m²
 Contrast 300:1
 I/O 1x SDI I/O on BNC
 1x CVBS I/O on BNC
 1x Tally on SUBD9

LCV 57X3R



Panel size 3x 5.7"
 Resolution 640 x 480
 Display area 116.2 x 87.2 mm
 Pitch (mm) 0.1815 x 0.1815
 Brightness 220 cd/m²
 Contrast 300:1
 Viewing angles H: 140° - V: 100°
 Inputs 1x CVBS on BNC
 Tally on DB9
 Outputs 1x CVBS on BNC
 Dimensions (WxHxD) 19" x 3U
 Power supply 12 VDC
 Consumption 36W

SDI



LCV 57x3R
rear panel



LCV 57x3R
front panel

SDI

LCV 57x3RFSDI
 Same specifications as **LCV 57x3R** above
 with SDI inputs on BNC.

AXRTO SERIES - RACK MOUNT VIDEO & GRAPHIC

AXRTO 70X2R



Panel size 2x 7"
 Resolution 800 x 480
 Display area (mm) 152.4 x 91.5
 Brightness 600 cd/m²
 Contrast 500:1
 Viewing angles H: 70/70° - V: 60/50°
 Inputs 1x CVBS on BNC
 1x s-video on mini-din
 1x VGA on HD15
 Dimensions (WxHxD) 19" x 3U x 95.5 mm
 Power supply 12 VDC
 Consumption 20W

SDI

LCV 70x2RFSDI
 Same specifications as **AXRTO 70x2R** above
 with SDI inputs on BNC and without VGA.

AXRTO 84X2R



Panel size 2x 8.4"
 Resolution 800 x 600
 Display area (mm) 170 x 128
 Brightness 350 cd/m²
 Contrast 500:1
 Viewing angles H: 60/60° - V: 60/40°
 Inputs 2x CVBS on BNC + 1 output
 1x s-video on mini-din
 1x VGA on HD15
 Dimensions (WxHxD) 19" x 4U x 71 mm
 Power supply 12 VDC
 Consumption 20W

SDI

LCV 84x2RFSDI
 Same specifications as **AXRTO 70x2R** above
 with SDI inputs on BNC and without VGA.

AXRTO 10R



Panel size 10"
 Resolution 800 x 600
 Display area 210 x 157 mm
 Pitch (mm) 0.264 x 0.264
 Brightness 350 cd/m²
 Contrast 400:1
 Viewing angles H: 65/65° - V: 55/55°
 Inputs 2x CVBS on BNC + 1 output
 1x s-video on mini-din
 1x VGA on HD15
 Dimensions (WxHxD) 19" x 5U x 53 mm
 Power supply 12 VDC
 Consumption 10W

AXRTO 12R



Panel size 12"
 Resolution 800 x 600
 Display area 246 x 184.5 mm
 Pitch (mm) 0.3075 x 0.3075
 Brightness 250 cd/m²
 Contrast 350:1
 Viewing angles H: 60/60° - V: 50/50°
 Inputs 2x CVBS on BNC + 1 output
 1x s-video on mini-din
 1x VGA on HD15
 Dimensions (WxHxD) 19" x 6U x 53 mm
 Power supply 12 VDC

AXRTO 15R - 15" version
AXRTO 17R - 17" version
AXRTO 19R - 19" version

AXCOM SERIES - LCD WITH BUILT-IN PC

AXCOM 15 / PC INTEGRE



Panel size	15"
Resolution	1024x768
Display area (mm)	304 x 228
Pitch (mm)	0.297 x 0.297
Brightness	250 cd/m ²
Contrast	500:1
Viewing angles	H: 65/65° - V: 55/65°
Dimensions (WxHxD)	400 x 320 x 78 mm
Power supply	12 VDC
Consumption	85W
CPU	Celeron 1.5GHz
RAM	512MB
HDD	80GB
Inputs	2x PS/2 + 4x USB
Communication	2x RJ45 + 3x RS232

AXCOM 84 - 8.4" version
AXCOM 10 - 10" version
AXCOM 12 - 12" version
AXCOM 17 - 17" version
AXCOM 19 - 19" version

AXCOM 15TR / PC INTEGRE & TACTILE



Touch panel	Resistive
Panel size	15"
Resolution	1024x768
Display area (mm)	304 x 228
Pitch (mm)	0.297 x 0.297
Brightness	250 cd/m ²
Contrast	500:1
Viewing angles	H: 65/65° - V: 55/65°
Dimensions (WxHxD)	400 x 320 x 78 mm
Power supply	12 VDC
Consumption	85W
CPU	Celeron 1.5GHz
RAM	512MB
HDD	80GB
Inputs	2x PS/2 + 4x USB
Communication	2x RJ45 + 3x RS232

AXCOM 84TR - 8.4" version
AXCOM 10TR - 10" version
AXCOM 12TR - 12" version
AXCOM 17TR - 17" version
AXCOM 19TR - 19" version

MPC PLV SERIES - DIGITAL SIGNAGE

MPC PLV 15 / LECTEUR DE MEDIAS INTEGRE



Panel size	15"
Resolution	1024 x 768
Display area	304 x 228 mm
Brightness	250 cd/m ²
Contrast	500:1
Viewing angles	H: 65/65° - V: 55/65°
Card Reader	1x Compact Flash 1x SD/MS/SM/MMC 1x Microdrive
Supported files	MPEG1/2/4 JPG - MP3
Speakers	2x2W - built-in
Dimensions (WxHxD)	360 x 290 x 52 mm
Power supply	100/240 VAC
Consumption	30W

MPC PLV 84 - 8.4" version
MPC PLV 10 - 10" version
MPC PLV 12 - 12" version
MPC PLV 17 - 17" version
MPC PLV 19 - 19" version

MPC PLV 20W / LECTEUR DE MEDIAS INTEGRE



Panel size	20" - wide format
Resolution	1366 x 768
Display area	444 x 250 mm
Brightness	450 cd/m ²
Contrast	600:1
Viewing angles	H: 80/80° - V: 60/80°
Card Reader	1x Compact Flash 1x SD/MS/SM/MMC 1x Microdrive
Supported files	MPEG1/2/4 JPG - MP3
Speakers	2x2W - built-in
Dimensions (WxHxD)	475 x 325 x 83 mm
Power supply	12 VDC
Consumption	46W

MPC PLV 17W - 17" version
MPC PLV 19W - 19" version
MPC PLV 26W - 26" version
MPC PLV 32W - 32" version

EYEZUP 1080P / SANDALONE FULLHD MEDIAPLAYER



Supported files	WMV9 HD MPEG1/2/4, JPG, MP3
Storage	CF type I & II
Outputs	1x HDMI 1x CVBS on RCA 1x YC on mini-Din 1x VGA on sub-D 15 1x YUV on 3 RCA 1x audio stereo on RCA
Resolution	SXGA in graphic mode 1080p in HDMI
Dimensions (WxHxD)	267 x 143 x 30 mm
Power supply	12VDC - 1.5A

EYEZUP 4 / SANDALONE MEDIAPLAYER



Supported files	MPEG1/2/4, JPG, MP3
Memory card	CF type I & II/SM MMC, MS&MSPRO
Outputs	1x CVBS on RCA 1x YC on mini-Din 1x VGA on sub-D 15 1x audio stereo on jack
Resolution	640x480
Dimensions (WxHxD)	150 x 100 x 25 mm
Power supply	5VDC - 2A

AXM SERIES - DESKTOP VIDEO & GRAPHIC

AXM 17TS



Panel size	17"
Resolution	1280 x 1024
Display area (mm)	338 x 270
Pitch (mm)	0.264 x 0.264
Brightness	300 cd/m ²
Contrast	800:1
Viewing angles	H: 85/85° - V: 80/80°
Inputs	1x CVBS + 1 output on BNC 1x s-video + 1 output on mini-din 1x YUV on RCA 1x audio + 1 output on RCA
Dimensions (WxHxD)	375 x 370 x 42 mm
Power supply	12 VDC
Consumption	45W

AXM 15TS - 15" version
AXM 19TS - 19" version
AXM 20TS - 20" version

AXM 15SOBK



Panel size	15"
Resolution	1024 x 768
Display area (mm)	304.1 x 228.1
Pitch (mm)	0.297 x 0.297
Brightness	230 cd/m ²
Contrast	200:1
Viewing angles	H: 160° - V: 160°
Inputs	1x CVBS on RCA 1x s-video on mini-din 1x DVI on DVI-F 1x audio on mini-jack (+1 output)
Dimensions (WxHxD)	404 x 393 x 162 mm
Power supply	12 VDC

AXM 17SOBK - 17" version

LCV SERIES - SMALL SIZE DESKTOP VIDEO: www.vity.com